



PHOTOS MAY SHOW OPTIONAL OR CUSTOMISED EQUIPMENT.

LINE TYPES



Dots

2 COMPONENT DOT APPLICATION (98:2)

From city areas to urban and interurban roads, the Borum Master 2000 can handle both smaller jobs and longer road stretches.

The BM 2000 CP D is an agile machine with excellent loading abilities and a turning radius of only 3.2 m. It allows for paint tank capacities of 440 L or 2 x 220 L.

The BM 2000 has a one-seat slidable drive and operator section for flexible working on the left or right side.

The Borum 2-component application equipment can be set to execute lines in widths between 10-30 cm. The equipment on this machine may be used for the application of profiled dots.

KNOWING THE BM 2000


OPERATOR SECTION

Quick and easy change from side to side for marking left and right.
Dual torque steering - good directional stability.
Cruise control can be added as optional equipment.

LINEMASTER COMPUTER



With the LineMaster Computer you can control up to 6 paint or spray guns, 6 bead guns and equipment with up to 24 shutters.
Moreover, it controls all these various sets of equipment in this ONE unit.

FULL REAR VIEW



CHASSIS

Solid double-frame construction



TECHNICAL SPECIFICATIONS

ENGINE	
Manufacturer	Kubota
Type	Turbo (Diesel)
Cooling	Water
Cylinder	4 stroke 2400 cm ³
RatedPower	44 KW
Approval	EU stage IIIA (type V2403-M-T-)/US Interim TIER 4
COMPRESSOR	
Compressor Capacity	Screw compressor. 1800 L/min @ 10 bar Integrated oil-cooling system. Air-cooler incl. water separator.
FILLING CAPACITIES	
Fuel tank capacity	50 L (diesel)
Hydraulic tank size	50 L
Bead capacity	115 L/170 kg. Pressurized (max 2.1 bars)
MATERIAL TANK	
Material Tank	440 L or 2 x 220 L
DRIVING PROPERTIES	
Turning radius	3,2 m
Steering	Dual torque steering
TRANSMISSION	
Hydrostatic transmission	For variable speed, forward/backwards
Speed	0-16 km/h
ELECTRICAL SYSTEM	
Electrical system	12 V / 150 Amp
CONTROL UNIT	
Borum LineMaster	Program up to 99 different line types. Organise lines in up to 30 marking programs. 8" display. Transfer of daily marking reports. See more detailed info.
COLOUR	
Colour	RAL 1007 (Other colours available on request)
DIMENSIONS	
Length	4150 mm
Width	1100 mm
Height	2465 mm

2-COMPONENT COLD PLASTIC (98:2) EQUIPMENT - GENERAL INTRODUCTION

Being equipped with an internal mixer for mixing of the paint and hardener and efficient cleaning system that is easily triggered from the machine's computer, the Borum 2-component cold plastic equipment is constructed to provide high quality road markings.

THE BORUM 2-COMPONENT COLD PLASTIC EQUIPMENT (LOW PRESSURE SYSTEM) CONSISTS OF:

1. Separate material tanks for:
 - Paint
 - Hardener
 - Solvent for cleaning
2. Feeder system with:
 - Pump that ensures the 98:2 ratio for the paint and hardener
 - Mixer for blending the paint and the hardener. The mixing of the material is done internally, so it is not affected by external factors as wind etc., as for external mixing
 - Pressure valves digitally controlled by Borum LineMaster computer. No need for mechanical adjustment while marking



LOW PRESSURE PUMP SYSTEM WITH INTERNAL MIXING FOR SECURING 98:2 RATIO

The pump system consists of a lobe type paint pump and gear type pump for hardener. The two pumps are driven by one hydraulic motor via chain and variable gearbox securing the 98:2 relation between paint and hardener.

The system is also equipped with a controller for performing the flushing of gun(s) and mixer.

BORUM VARIO RETAINER FOR EASY EQUIPMENT SWITCH

The Borum Vario Retainer provides a unique possibility to interchange between applications in a very short time, with very few standard tools. When the work is done, the retainer and application equipment can be easily stowed under the machine.

The retainer makes it possible to use all application equipment in different positions on the machine.

Easily slidable from side to side for an optimal working position. Ground distance is maintained by retainer wheel to ensure a constant road marking width.

ALARMS


- Alarm when hardener does not flow during marking work. This helps to avoid non-cured markings to be applied
- Alarm when there is a break in the marking works which is longer than set in the computer. This notifies you to clean the system before material cures inside the equipment.



THIS MACHINE IS EQUIPPED WITH

DOT APPLICATION, 2-COMPONENT 98:2, STRUCTURED MARKING

For making 2-component dotted lines in all standard line widths.



The Borum 2-component DOT is a flexible system of building blocks, which makes it possible to put together exactly the required application size.

The line width can be 10-30 cm, the line thickness can be from 1.5 to 5 mm, and the gap between the dots is 17 mm. Dot thickness is usually around 3-4 mm.

The marking speed can be 4-5 km/h depending on the conditions, e.g. material, dot size, operator's experience, etc.

DOT basic module includes 6 rows of DOTs. With built-in mixer and pneumatic valves for paint, hardener and cleaning solvent, all controlled from the LineMaster.

Maximum of 18 dots across the head, separate cleaning extension is needed for dot heads wider than 13 dots.

Recommended quantity dots/m 15-20, controlled in the LineMaster computer. Recommended paint viscosity > 8500 cp.

AS AN OPTION YOU CAN ALSO ADD ONE OF THE FOLLOWING APPLICATION EQUIPMENTS

2-COMPONENT SPRAY 98:2

The machine can be supplied with one or two spray guns and possibility to apply line widths of up to 20 cm (8 inch) per gun. Please notice that restrictions apply when 2 guns are mounted.

2-COMPONENT 98:2, EXTRUDER 98:2 (STRUCTURED MARKING)

The extruder is ordered for the specific line width. Available line widths are 10, 12, 15, 17, 20, 22, 24, 25, 30 (4, 5, 6, 7, 8, 8.5, 9, 9.5, 10, 12 inch.) Provided with quick connector to the mixer head for easy exchange of head.

2-COMPONENT 98:2, AGGLOMERATE APPLICATION (STRUCTURED MARKING)

Agglomerate needle roller available in a standard width of 30 cm (11.8 inch). It must be mounted under extruder unit. Line size depends on the extruder.

*NB! There are limitations when using the same machine for both sprayed and profiled applications:

- Thorough cleaning of material tanks is needed when changing material
- The pump will be worn when using the rougher material for profiled markings, so after a while the pressure will not be sufficient for a proper result with spray.

PRESSURIZED STAINLESS STEEL TANK



PRESSURIZED MATERIAL TANK FOR 2-COMPONENT

Pressurized material tank and filters in stainless steel for water and ammonium based paints. Option for black steel tanks.

The material tank has a filling system with two filling holes. This makes the filling process very easy to manage.

AGITATOR (MIXER)

Driven by hydraulic motor and with manually operated reversing valve.

EASY-TO-USE CLEANING SYSTEM

The cleaning system is formed by a solvent tank for cleaning of mixer-head, hoses and paint guns. The system is activated via the Borum LineMaster computer. The cleaning process is an automated preset sequence ensuring the correct valves are opening/closing.

36L (79 lb wt.) pressure solvent tank for cleaning of mixer-head, hoses and paint guns.

Stainless steel, max 8.5 bar (123 psi).

NB! When working with 2-component whenever the application is stopped, application equipment has to be cleaned from the cold plastic mixture within a few minutes.

LINEMASTER FEATURES

The Borum LineMaster control unit is an easy way of setting and controlling your line marking jobs. The LineMaster is attached to the operator's section of the machine and gives you full control of all your line marking tasks, from line application and pre-marking to reporting and invoicing.

It is possible to store up to 99 different line types, and to arrange these in up to 30 different marking programs. You are also able to pre-set line widths, line types, colours and combinations to have them ready for marking, and can instantly adjust them on the go.

Furthermore, you are able to view the status of various parts of the machine (e.g. compressor) on the computer screen that will help with correctly maintaining the machine and avoiding break downs.

2-COMPONENT MATERIAL ADVANTAGES

The 2-component application material is a great solution for ensuring reliable line markings in areas with dense traffic. With 2-component material you get a wear resistant road marking with good visibility, durability and little dirt pick up.



The challenge with 2-component cold plastic material is that once it is mixed it needs to be applied on the road right away. Even though Borum machines are designed to mix the materials as late as possible in the application process, you will need to pay attention to the time frame you have, before the material cures inside the machine / equipment.



TYPICAL USES:

Great solution for ensuring reliable line markings in areas with dense traffic.



LEARN MORE

Find out more in the Borum Knowledge Lab.

ADDITIONAL EQUIPMENT

The additional equipment can be mounted on the machine according to your requirements. They are not necessary for the running of the machine but add to the comfort of the machine driver or to the functionality of the machine.



Hand paint gun



Ejector filling of bead tank



Air drier for bead tank



Fixed pointer
With hydraulic lifting system



Remote control for BM LineMaster



Cone holder



Pointer turning with steering
With hydraulic lifting system



Sunshade with 1 rotating light



Cruise control



BORUM ONLINE



Bead alarm mounted on bead gun



Bar with pneumatic lift for mounting warning lights
(Comes without lights)



Pre-marking system with paint gun



Airknife



Pre-marking system with paint can



Hydraulic broom